

RESPONSE  
SN 09/677,060  
PAGE - 4 of 20 -

**Amendments to the Claims**

- Sub B1
1. (~~Currently Amended~~) A method of transporting bifurcated voice and signaling data over a network, comprising the steps of:  
identifying, for each communication link to be established respective signaling data and voice data; and  
transmitting said signaling data via a first ~~medium~~ network and said voice data via a second ~~medium~~ network, wherein the first network is different from the second network.
  2. (~~Currently Amended~~) The method of claim 1, wherein said first ~~medium~~ network is a wireless network.
  3. (~~Currently Amended~~) The method of claim 1, wherein said second ~~medium~~ network is a data packet network ~~medium~~.
  - AS
  4. (Original) The method of claim 1, further comprising the steps of:  
communicating said signaling data to a switch.
  5. (Original) The method of claim 1, further comprising:  
communicating said voice data to a switch.
  6. (Original) The method of claim 3, wherein said voice data is subject to compression processing compatible with a wireless network.
  - Subs B1
  7. (Original) The method of claim 5, wherein said step of communicating is made via a base station system.
  8. (Original) The method of claim 5, wherein said step of communicating is made via a packet/circuit switch.

248587-1

RESPONSE  
SN 09/677,060  
PAGE - 5 of 20 -

9. (Original) The method of claim 1, wherein said steps of identifying and transmitting are performed via a Media Terminal Adapter-Cellular Transceiver (MTA-CT) having integrated MTA and CT portions.
10. (Original) The method of claim 1, wherein said steps of identifying and transmitting are performed via a Media Terminal Adapter-Cellular Transceiver (MTA-CT) having non-integrated MTA and CT portions.
11. (~~Currently Amended~~) In a communication system for transporting bifurcated voice and signaling traffic over a network, a method comprising the steps of:  
segregating signaling traffic and related voice traffic including information useful in establishing a communications link for transporting said voice traffic between a calling party and a called party; and  
transmitting said voice traffic via said communications link established by a controller, said voice traffic and said signaling traffic being carried via different communication ~~channels~~ networks.
12. (~~Currently Amended~~) The method of claim 11, wherein one of said communication ~~channels~~ networks is a data packet network.
13. (Original) The method of claim 12, wherein said voice traffic is carried by said data packet network.
14. (Original) The method of claim 13, wherein said voice traffic is subject to compression processing compatible with a wireless network.
15. (~~Currently Amended~~) The method of claim 11, wherein one of said ~~second~~ communication ~~channels~~ networks is a wireless network

RESPONSE  
SN 09/677,060  
PAGE - 6 of 20 -

16. (Original) The method of claim 15 wherein said signaling traffic is carried by said wireless network.

17. (Original) The method of claim 11, wherein said controller is a switch.

18. (Original) The method of claim 11, wherein said signaling traffic is transmitted to said controller via a base station system.

Subs  
B1  
19. (Original) The method of claim 11, wherein said voice traffic is communicated to said controller via a packet/circuit switch.

20. (Original) The method of claim 11, wherein said steps of segregating and transmitting are performed via a Media Terminal Adapter-Cellular Transceiver (MTA-CT) having integrated MTA and CT portions.

21. (Original) The method of claim 11, wherein said steps of segregating and transmitting are performed via a Media Terminal Adapter-Cellular Transceiver (MTA-CT) having non-integrated MTA and CT portions.

22. (~~Currently Amended~~) The method of claim 11 further comprising the step of: switching the voice traffic to the same communication ~~channel~~ network as the signaling traffic when loss of local power is detected.

23. (~~Currently Amended~~) In a communication system for transporting bifurcated voice and signaling traffic between a calling party and called party, a method comprising the steps of:

identifying a call request;

establishing a signaling link to a switch via a first transport ~~medium~~ network and

RESPONSE  
SN 09/677,060  
PAGE - 7 of 20 -

establishing a voice path to said switch via a second transport ~~medium~~ network responsive to a determination that said called party answers, said first transport network being different from said second transport network.

24. (Currently Amended) The method of claim 23, wherein said first ~~medium~~ network is a wireless network.

25. (Currently Amended) The method of claim 24, wherein signaling data traffic is transmitted over said wireless network.

26. (Currently Amended) he method of claim 23, wherein said second ~~medium~~ network is a data packet network.

27. (Currently Amended) The method of claim 26, wherein voice data traffic is communicated over said data packet network.

28. (Currently Amended) The method of claim 27, wherein said voice data traffic is subject to compression processing compatible with a wireless network.

29. (Currently Amended) The method of claim 23 further comprising the step of:  
switching the voice data traffic to the same ~~medium~~ network as the signaling data traffic when loss of local power is detected.

30. (Original) The method of claim 23, wherein said steps of identifying and said first and second steps of establishing are performed via a Media Terminal Adapter-Cellular Transceiver (MTA-CT) having integrated MTA and CT portions.

31. (Original) The method of claim 23, wherein said steps of identifying and said first and second steps of establishing are performed via a Media Terminal Adapter-Cellular Transceiver (MTA-CT) having non-integrated MTA and CT portions.

RESPONSE  
SN 09/677,060  
PAGE - 8 of 20 -

- Sub B1
32. (Original) A ~~communications system~~ comprising:  
a device for providing bifurcated voice and signaling traffic over a network; and  
a ~~packet/circuit switch~~ for converting data packets to circuit switched traffic.
33. (Original) The communications system of claim 32, wherein said device is a Media Terminal Adapter-Cellular Transceiver (MTA-CT) having non-integrated MTA and CT portions.
34. (Original) The communications system of claim 32, wherein said device is a Media Terminal Adapter-Cellular Transceiver (MTA-CT) having integrated MTA and CT portions.
35. (Currently ~~Amended~~) A computer readable medium storing a software program, that when executed by a computer, causes the computer to perform a method comprising:  
segregating signaling traffic and related voice traffic including information useful in establishing a communications link for transporting said voice traffic between a calling party and called party; and  
transmitting said voice traffic via said communications link established by a controller, said voice traffic and said signaling traffic being carried via different communication channels networks.
36. (Original) The computer readable medium of claim 35, wherein said controller is a switch.
37. (Original) The computer readable medium of claim 35, wherein said signaling traffic is communicated via a wireless network.
38. (Original) The computer readable medium of claim 35, wherein said

RESPONSE  
SN 09/677,060  
PAGE - 9 of 20 -

voice traffic is communicated via a data packet network.

39. (Original) The computer readable medium of claim 38, wherein said voice traffic is subject to compression processing compatible with a wireless network.

---